



NetFORCE-18XPR[™]

HARSH - ENVIRONMENT COMPUTER

Supporting high-resolution presentation of critical data, Citadel's NetFORCE-18XPR™ industrial systems deliver rugged computing horsepower and full 1920 x 1080 HD graphics.



NetFORCE-18XPR

Our NetFORCE-XPR[™] series of rugged industrial computers represents years of field-proven refinement driven by our commitment to deliver market-leading performance, reliability and value.

These rugged fully-sealed systems deliver reliable horsepower in your most challenging harsh-environments. Their advanced 64-bit quad-core CPU, high-performance graphics, 'glove compatible' touch screen and bright high-visibility displays offer an outstanding level of performance and operator convenience.

A wide-input DC-power system with battery backup keeps your applications up-and-running. NetFORCE-XPR[™] systems withstand extremes of temperature, physical shock, vibration and environmental contaminants common to heavy industrial and weather-exposed installations.

- Advanced 64-bit quad-core CPU supporting 16-Gbytes DDR3 DRAM
- Enhanced 18.5" HD display / 1920 X 1080 / 16-million colors
- Intel dual-band Wi-Fi 802.11abgn / 802.11ac / Bluetooth v4.1 / CCX
- Industry standard 10/100/1000 Industrial Gigabit Ethernet
- 12/24 60 VDC power system with internal UPS battery back-up
- Fully sealed NEMA-4 / IP-66 water-tight aluminum enclosure

- Rugged, fast solid-state 256-Mbyte+ SSD mass storage
- High-resolution 'glove compatible' touch screen
- Rugged, high-performance 'no break' flexible antennas
- mini-PCI Express expansion slot [CANBUS / GPS / custom I/O, etc.]
- Cold-start system preheater and integrated 'no frost' display options
- O/S compatibility: Windows 7 Pro/WES, Windows 10 IoT / Linux, etc.

Bright 1920 x 1080 HD display

Rugged aluminum enclosure fully sealed to NEMA 4 / IP-66

md 1 / + = 1 **ORS-RIGSENTRY** STATUS PROFIL 15:36:00 UMP SPM1 -----F1 PUMP SPM2 MUD VOL 1298 F2 BIT STATUS ENG F3 BLOCK HEIGHT 18.1 HOOK LOAD 257.001 Depth -ft: 19978.3 BIT POS -ft: 199772 **F4** BIT ROP 7.006 VERAGE ROP 6.66 BIT DATA CYCLE TRACK 001 TRACK 005 BIT WEIGHT 38.89 RUN COM TRACK 002 TRACK 006 CAM 1 CAM 2 NETWORK STATUS TRACK 003 TRACK 007 19.9 STOP CAM 3 CAM 4 TRACK 004 TRACK 008 PIPE TALLY SET DEPTH/BIT ZERO GL PVT TOUR HOLD PLOT BY DEPTH ZERO BIT WT TOOLS OTHER DATA SETUP CHARTS REPORTS SETUR RESET WARNINGS DISABLED CAM 1 CONA ALARMS ENABLED 0 User-friendly status indicators Easy full-range dimming controls

NetFORCE-18XPR

System CPU and Memory

Advanced QUAD-CORE 64-bit CPU supporting up to 16-Gibytes DDR3 System DRAM

Enhanced LCD Display & Touchscreen

Resolution: 1920 X 1080 HD --- Brightness Enhanced / Sunlight readable options Viewing Area: 18.5" diagonal with high-resolution 'glove compatible' touchscreen Video-blanking: automatic vehicle in-motion screen-blanking fully-supported

Mass Storage and Networking

High-performance SSD: 256-Mbytes (or more) Wireless Networking: INTEL dual-band 802.11abgn / 802.11ac / Bluetooth v4.1 / Cisco CCX Industrial Gigabit Ethernet: 10/100/1000 (cabled)

System Expansion

Internal mini-PCI Express slot accepts industry standard options for I/O expansion such as: CANBUS / GPS navigation / analog & digital I/O, etc.

Fully-sealed NEMA-4 / IP-66 Power & I/O Industrial Interconnects

Power ON/OFF | DC-PWR IN | Keyboard & mouse | Dual USB | Industrial Ethernet | Optional External Horn | RS-232 COM ports | External Coax Antenna Connector, etc.

Input Power

24 to 60 VDC (nominal) 12 VDC with optional cable adapter 72 VDC & above (multiple high-voltage options) 90-220 VAC 50/60 Hz. Universal AC Adapter Total Input Power: < 60 watts (maximum) / Intenal UPS (standard)

Environmental Specifications

Rating: UL50E Type-4 / NEMA-4 / IP-66 Temperature: -20 C to +50 C (operating) Humidity: 0% - 95% (non-condensing) Vibration: MIL-810F 2.0 G (15-1000 Hz.) (operating) EMI/RFI: FCC Part-15 / MIL-STD-461E

Mechanical Specifications

Mounting: 2.5" Flex-mount ball and 75mm VESA mount Width: 18.75" (36.85 cm) Height: 12.00" (30.5 cm) Depth: 3.50" (8.89 cm) Weight: ~17.5 lbs. (8.0 kg) (typical)

Rugged die-cast aluminum enclosure fully sealed to NEMA 4 / IP-66



Fully sealed power and I/O certified to NEMA 4 / IP-66 with custom I/O options available

Netforce-18XPR

INSERT MECHANICAL OUTLINE DRAWING

OVERALL DIMENSIONS:

18.75" width x 12.00" height x 3.50" depth

Since 1979, Citadel Computer Corporation has focused on the design and manufacturing of rugged industrial computers for challenging harshenvironment industrial and military applications.

Our systems combine state-of-the-art processing technology with practical real-world engineering to deliver reliable computing horsepower that withstands extremes of temperature, physical shock, vibration and exposure to the elements.

As reliable platforms performing a wide spectrum of tasks, Citadel systems are in service around globe supporting advanced processes, research and control for many of the world's leading companies.



CITADEL COMPUTER CORPORATION 16 Columbia Drive Amherst, NH 03031-2304 USA

TEL: 603-672-5500 FAX: 603-672-5590

www.citadelcomputer.com

The specifications, performance characteristics and information contained herein are believed to be complete and accurate at the time of publication. However, Citadel Computer Corporation offers ongoing product improvements and expressly reserves the right to correct, update and/or modify product specifications without prior notice.

Citadel Computer Corporation[™] and Citadel NetFORCE-18XPR[™] are trademarks of Citadel Computer Corporation © 2019.

All rights reserved.

United States and international patents pending.

© 2019 CITADEL COMPUTER CORP. / NF18XPR - 2019A